

December 18, 2009

Type: HAA Polyester



ALESTA AR300*

Number: HFB2100B2

AR300 AP Black Anodic Matt

Alesta Group Code: AE20104000720

POWDER PROPERTIES

Name:

ASTM D5965-96, C	Specific Gravity	1.4 ± 0.05
	Theoretical Coverage	137 ft2/lb/mil
ASTM D3451-92, 13	Mass Loss During Cure	< 1%
	Recommended Shelf Life:	12 Months @ 75 F

COATING PROPERTIES

ASTM D523-89	Gloss at 60°	15-25
DPC TM 10.219	PCI Powder Smoothness	7
ASTM D2454-95	Overbake Resistance, Time	100%
ASTM D3363-92a	Pencil Hardness	
ASTM D2794-93	Dir / Rev Impact, Gardner	20 / 20 in/lbs
ASTM D3359-97	Adhesion, Cross Hatch	5B Pass
ASTM D522-93a	Flexibility, Mandrel	1/4 in. dia., no fracture
ASTM B117-97	Salt Spray	1,000 hrs
UL DTOV2 Organic Coating	Steel Enclosures, Elect. Eq.	Recognized
Qualicoat	Approved	P-0720

APPLICATION

Electrostatic Spray, Cold Substrate: Aluminum Pretreatment: Solvent Clean **CURE SCHEDULE:**

(Time at substrate temperature) 12 Minutes @ 374F

FILM THICKNESS: 2.7-3.5 Mils

*This product meets the requirements of AAMA 2603.

This is an Axalta Powder Coating Systems USA France SAS product. Product is recommended for outdoor architectural applications. Product complies with European Directive RoHS n°2002/95/CE of the 27th of January 2003

9800 Genard Rd. Houston, TX 77041-7624 4130 Lyman Dr. Hilliard, OH 43026-1213 1-800-247-3886 1-800-667-9610

fax: 713-939-4027 fax: 614-771-4139 Prepared 8/2/2013

POWDER TOUGH ISO 2001

WARRANTY POLICY: Seller certifies that all coatings delivered to Customer in unopened factory filled containers meet all pertinent quality standards presented in its current published literature. Since matters of surface preparation, application procedures, curing procedures and other local factors that affect coating performance are beyond Seller's control, Seller assumes no liability for coating failure other than to supply replacement material for a coating material proven to be defective. Customer will determine suitability of this product for its use and thereby assume all risks and liabilities in connection therewith. Seller will not be liable for any injuries, damages or other losses derived, directly or indirectly, from or as a consequence of Customer's use of the product. SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, RELATING TO ITS PRODUCTS AND THEIR APPLICATION, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES.