

Technical Information Sheet

ALESTA AR300*

Number: *HFHR34*S8

Name: RAL 7009 HAA

Alesta Group Code: AE80007000616

August 7, 2013 Type: <u>HAA Polyester</u>

<u>AE80007000616</u>

POWDER PROPERTIES

| ASTM D5965-96, C | Specific Gravity Theoretical Coverage | 1.55 ± 0.05 124 ft2/lb/mil |
|-------------------|--------------------------------------------------|-------------------------------|
| ASTM D3451-92, 13 | Mass Loss During Cure Recommended Shelf Life: | < 1% 12 Months @ 75 F |

COATING PROPERTIES

| ASTM D523-89 | Gloss at 60° | 75-85 |
|--------------------------|--------------------------------------------|---------------------------|
| DPC TM 10.219 | PCI Powder Smoothness | 7 |
| ASTM D2454-95 | Overbake Resistance, Time | 100% |
| ASTM D3363-92a | Pencil Hardness | 2H |
| ASTM D2794-93 | Dir / Rev Impact, Gardner | 160 / 160 in/lbs |
| ASTM D3359-97 | Adhesion, Cross Hatch | 5B Pass |
| ASTM D522-93a | Flexibility, Mandrel | 1/8 in. dia., no fracture |
| ASTM B117-97 | Salt Spray | 1,000 hrs |
| UL DTOV2 Organic Coating | Steel Enclosures, Elect. Eq. | Recognized |
| AAMA 2603-02 | Organic Coatings on Aluminum Extrusions | Passed |

APPLICATION

Electrostatic Spray, Cold Substrate: 0.032 in. CRS Pretreatment: Bonderite® 1000, Parcolene® 60

*This product meets the requirements of AAMA 2603.

CURE SCHEDULE:

(Time at substrate temperature) 10 Minutes @ 375F or 15 Minutes @ 350F **FILM THICKNESS:** 2.0-3.0 Mils

This coating has been developed to meet or exceed the requirements of AAMA 2603 on architectural aluminum components.

9800 Genard Rd. Houston, TX 77041-7624 4130 Lyman Dr. Hilliard, OH 43026-1213

1-800-247-3886 1-800-667-9610

-3886 fax: 713-939-4027 -9610 fax: 614-771-4139

WARRANTY POLICY: Seller certifies that all coatings delivered to Customer in unopened factory filled containers meet all pertinent quality standards presented in its current published literature. Since matters of surface preparation, application procedures, curing procedures and other local factors that affect coating performance are beyond Seller's control, Seller assumes no liability for coating failure other than to supply replacement material for a coating material proven to be defective. Customer will determine suitability of this product for its use and thereby assume all risks and liabilities in connection therewith. Seller will not be liable for any injuries, damages or other losses derived, directly or indirectly, from or as a consequence of Customer's use of the product. SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, RELATING TO ITS PRODUCTS AND THEIR APPLICATION, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES.

4027 Powder 4139 Tough ISO 9001