Technical Information Sheet



Number: *RFJ202S3* <u>December 12, 2007</u>

Name: KL Primer Type: <u>Epoxy-Polyester Hybrid</u>

Alesta Group Code: EP20008000012

POWDER PROPERTIES

ASTM D5965-96, C Specific Gravity 1.62 ± 0.05

Theoretical Coverage 119 ft2/lb/mil

ASTM D3451-92, 13 Mass Loss During Cure < 1%

Recommended Shelf Life: 12 Months @ 75 F

COATING PROPERTIES

ASTM D523-89 Gloss at 60° 30-50 **DPC TM 10.219** PCI Powder Smoothness 8 ASTM D2454-95 Overbake Resistance, Time 100% ASTM D3363-92a Pencil Hardness H-2H ASTM D2794-93 Direct Impact, Gardner 160 in/lbs ASTM D3359-97 Adhesion, Cross Hatch 5B Pass

ASTM D522-93a Flexibility, Mandrel 1/8 in. dia., no fracture

ASTM B117-97 Salt Spray 1,000 hrs

UL DTOV2 Organic Coating Steel Enclosures, Elect. Eq. Recognized

APPLICATION

Electrostatic Spray, Cold Substrate: 0.032 in. CRS

Pretreatment: Bonderite® 1000, Parcolene® 60

CURE SCHEDULE:

(Time at substrate temperature)
18 Minutes @ 400F

FILM THICKNESS: 1.5-2.0 Mils

Prepared 6/11/2013

9800 Genard Rd. Houston, TX 77041-7624 4130 Lyman Dr. Hilliard, OH 43026-1213 1-800-247-3886 fax: 713-939-4027 1-800-667-9610 fax: 614-771-4139

1027

DER TED GH"ICOUNT

4130 Lyman Dr. Hilliard, OH 43026-1213 1-800-667-9610 fax: 614-771-4139 FOUR SOCION SOCIETA SO

WARKANTY POLICY: Selier certifies that all coatings delivered to Customer in unopened factory filled containers meet all pertinent quality standards presented in its current pulpinshed literature. Since matters of surface preparation, application procedures, curing procedures and other local factors that affect coating performance are beyond Seller's control, Seller assumes no liability for coating failure other than to supply replacement material for a coating material proven to be defective. Customer will determine suitability of this product for its use and thereby assume all risks and liabilities in connection therewith. Seller will not be liable for any injuries, damages or other losses derived, directly or indirectly, from or as a consequence of Customer's use of the product. SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, RELATING TO ITS PRODUCTS AND THEIR APPLICATION, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES.

