

Equipment

Designation	Cartridge	Fluid Inlet fitting	Suction	Drain rod	Atomizing air regulator	Fluid pressure regulator	Filter pump output	Hoses	Part number
35C50 F1/2 wo Filter wo Rod	MB-A	F1/2 BSP	-	-	1	•	-	-	151148000
35C50 M26x125 wo Rod wo filter	MB-A	M26x125	-	-	1	•	-	-	151148050
35C50 M26x125 + Rod wo Filter	MB-A	M26x125	D25	-	1	•	-	-	151148250
35C50 M26x125 + Rod + Filter	MB-A	M26x125	D25	•	1	•	•	-	151148100
35C50 M26x125 wo Filter Wo Rod	MB-A	M26x125	-	-	-	•	-	-	151148200
35C50 F1/2 wo Filter wo Rod	MB-A	F1/2 BSP	-	-	-	•	-	-	151148150
35C50 M126x125 + Rod wo Filter	MB-A	M26x125	D25	-	-	•	-	-	151148300
35C50 M26x125 Filter + Rod	MB-A	M26x125	D25	•	-	•	•	-	151148350

Kits

Designation	Maximum output pressure(bar (psi))	Gun type	Tip	Hoses included	Swivel fitting	Mounting	Packing material	Output filter	Suction rod	Part number
PACK 35C50 W/M MBA SUC D25 XCITE®+240 TWIST H7.5+12.114 NO FI	210 (3045)	Xcite®+240	12-114	7.5 m (24 ft)	•	Wall	MB-A	-	Ø 23	151148400
PACK35C50 W/M MBA SUC D25 FILTER XCITE®+240 TWIST H7.5+12.114	210 (3045)	Xcite®+240	12-114	7.5 m (24 ft)	•	Wall	MB-A	•	Ø 23	151148450
PACK 35C50 2G W/M MBA SUC D25+FIL 2/ XCITE®+240+2/09114+2/H7.5	210 (3045)	2 x Xcite®+240	2 x 09-114	2 x 7.5 m (24 ft)	2	Wall	MB-A	•	Ø 23	151148650

35C50 Airmix®

Paint pump

Airmix® / Pumps



AIRMIX® PRODUCTIVITY FOR ALL

- Designed for long-lasting industrial use
- Fast color changes with minimum solvent consumption
- Simple design to minimize maintenance time and operation

Markets



13 chemin de Malacher - CS 70086
38243 Meylan Cedex - FRANCE
Phone: +33 (0)4 76 41 60 60 - Fax: +33 (0)4 76 41 60 90
www.sames.com

Sames reserves the right to modify its equipment or specifications without further notice. Document, products and pictures shown are not contractual. Attest is a registered trademark: FR n° 1 222 301 - 202305 - 573 786 002 (NA LT 999-400-344)

BOND • PROTECT • BEAUTIFY



35C50 Airmix®

Paint pump

The 35C50 Airmix® paint pump ensures constant and pulse-free delivery for superior, industrial finishing.

The **35C50 Airmix® paint pump** will deliver excellent performance and outstanding benefits due to our 90 plus years on knowhow. With a powerful air motor, the 35C50 can feed up to (2) Airmix® or (2) SFlow™ Airless® spray guns. It can handle material viscosities from 20 cps up to 5000 cps with very low air consumption. It comes with an optimized fluid section volume for fast colour changes with minimal material loss.

The **35C50 Airmix® paint pump** packages are available in wall-mount versions or cart mounting as an option. Packages are available with (1) Xcite® 240 bar Airmix® manual spray gun equipped with a spray tip and 7.5 m (25ft) air and fluid hoses. An Airless® version with the SFlow™ spray gun along with a Skill™ for Airless Fine Finish applications is also available (see dedicated page). A large variety of options are available to meet all customer requirements.



Technical data table

Designation	Value	Unit: metric (US)
Pressure Ratio	35	
Maximum Fluid Pressure	210 (3000)	bar (psi)
Recommended Fluid Output	1500 (0.4 gal/min)	cc/mn (cfm)
Maximum Fluid Output	3000 (0.8 gal/min)	cc/mn (cfm)
Maximum Air Pressure	6 (87)	bar (psi)
Air Consumption	15	m³/h (cfm)
Maximum Temperature	60 (140)	°C (°F)
Fluid Output at 30 cycles/mn	1.5 (0.4)	l/min (gal/mn)
Fluid Volume per Cycle	50 (0.013 gal)	cc
Free Flow Rate	5 (1.3)	l/mn (gal/mn)
Fluid Output at 15 cycles / mn	750 (0.19 gal/min)	l/mn (gal/mn)
Seal Packings	PE UHMW	
Height	58.5 (23)	cm (in)
Width	23.5 (9.05)	cm (in)
Depth	23.5 (9.05)	cm (in)
Wetted Shares: Stainless Steel	♦	
Weight	8	kg (lbs)

sames kremlin




Technologies



Cup Lub



2 Ball



MBA cartridge



Triple Chrome Layer



Description

Performance

- 1 Quiet and balanced air motor for constant delivery
- 1 There is minimal pulsation due to quick air motor change over at low air pressures
- 2 Stainless-steel fluid section compatible with a wide range of materials including water-based paints
- 3 Designed to eliminate dead zones for quick color changes
- ♦ Pulse-free for a superior finish
- ♦ Able to flush and prime at very low air pressures (0.6 bar/8.5 psi)

Productivity

- 3 Large foot valve to handle high viscosity materials up to 5,000 cPs - carbide seat
- 4 Small fluid section, minimal material loss during color changes
- 5 Closed construction decreases the risk of injuries and protects the lubricant from external contamination
- 5 Leak indicator weep hole for fast visual inspection
- 6 Easy rotating outlet fitting to fit various configurations

Sustainability

- 1 Stall-free Differential Air Motor won't ice up
- 3 Easy to service with direct access to the suction valve
- 4 Single piece built-in cartridge with no dead zone
- 6 Easy coupling for a quick disassembling
- ♦ Mobile seal located on the piston ensures the cleaning of the fluid section internal wall while the pump is in operation
- ♦ Low maintenance, no external air distributor assembly. 45% fewer parts vs competition
- ♦ Triple chrome-plated piston parts compatible with most materials
- ♦ Magnetic reversing valve to eliminate pump surge
- ♦ Reduced spare parts: 50% fewer parts vs competition

