Equipment

Designation	Technology	Nozzle size	Air consumption (m3/h)	Fluid output (cc/mn)	Max fan width at 20cm (8in)	Part number
Gun FPro S CONV Solo	CONV	-	-	-	-	135780000
Gun FPro \$ CONV-12-Mvb + aluminum cup	CONV	1.2 mm (0.047 in)	26.5 m3/h (15.6 cfm)	120 cc/mn (4.05 oz/mn)	20cm - 30cm (8in - 12in)	135780312
Gun FPro \$ CONV-15-Mvb + aluminum cup	CONV	1.5 mm (0.059 in)	26.5 m3/h (15.6 cfm)	215 cc/mn (7.3 oz/mn)	20cm - 30cm (8in - 12in)	135780315
Gun FPro \$ CONV-18-Mvb + aluminum cup	CONV	1.8 mm (0.071 in)	26.5 m3/h (15.6 cfm)	284 cc/mn (9.6 oz/mn)	20cm - 30cm (8in - 12in)	135780318
Gun FPro \$ CONV-23-Lvb + aluminum cup	CONV	2.3 mm (0.091 in)	27.2 m3/h (16 cfm)	340 cc/mn (11.5 oz/mn)	30cm - 40cm (12in - 16in)	135780423
Gun FPro S CONV-27-Lvb + aluminum cup	CONV	2.7 mm (0.106 in)	27.2 m3/h (16 cfm)	405 cc/mn (13.7 oz/mn)	30cm - 40cm (12in - 16in)	135780427

Accessories

Desig	gnation	Capacity	Part number
Com	plete Alu Suction cup for FPro S	1 L	138.400.000

Spare Parts

Designation	Part number
Pack of filters (200µm) (x4)	138.310.300
Aircap FPro S Conv-23 27-Lvb	132.780.400
Aircap FPro S Conv-07 22-Mvb	132.780.300
Projector FPro \$ CONV-27-Lvb	131.780.427
Projector FPro \$ CONV-23-Lvb	131.780.423
Projector FPro S CONV-18-Mvb	131.780.318
Projector FPro \$ CONV-15-Mvb	131.780.315
Projector FPro S CONV-12-Mvb	131.780.312
Repair set for FPro S	129.780.901
Kit Suction booster valve	129.780.025
Seal kit	129.130.901
Kit Standard valve	129.030.020



13 chemin de Malacher - C\$ 70086 38243 Meylan Cedex - FRANCE Phone: +33 (0)4 76 41 60 60 - Fax: +33 (0)4 76 41 60 90 www.sames.com



FPro S Airspray

Conventional manual suction spray gun

Airspray / Manual Guns



PROFESSIONAL FINISHING FOR ALL PAINTERS!

- Breakthrough in Airspray technology
- Brand new suction cup options

Markets



BOND • PROTECT • BEAUTIFY



FPro S Airspray

Conventional manual suction spray gun

Perfectly balanced, the FPro S suction paint spray gun provides a superior finish for all levels of painters. Sames offers the largest range of spray guns and accessories for all FPro applications in high-end finishing markets.

FPro S Suction Feed - The New Standard in Airspray: In 1925 **Sames** created Airspray technology. In 2017, we reinvented a technique to atomize paint with patented innovations for the Airspray market. How did we do this? We developed a new Vortex based on decades of experience with prestigious customer applications.

The **PATENTED Vortex** spins the paint pre-atomizing it resulting in a homogeneous spray pattern that allows for excellent penetration on complex-shaped parts. The pre-atomization of the rotating paint produced by the Vortex allows for lower atomizing air with the same excellent finish and less bounce back maximizing transfer efficiency.



Technical data table

Designation	Value	Unit: metric (US)
Maximum Fluid Outlet	750 (26.3)	cc/min (oz/min)
Minimum Fluid Outlet	200 (7)	cc/min (oz/min)
Maximum Air Pressure	6 (87)	bar (psi)
Recommended Air Pressure (min)	2.5 (36) - 3.5 (51)	bar (psi)
Air Consumption	23 (13.5) - 29.7(17.5)	m3/h (cfm)
Maximum Fluid Temperature	50 (122)	°C (°F)
Air Inlet	M 1/4" NPS	
Fluid Inlet	M 3/8" NPS	
Ph	5-8	
Transfer Efficiency CONV	66	%
Weight	480 (16.9)	g (oz)









Paint Vortex for spraygun

Airspray Conventional

Description

Performance

- $\boldsymbol{1}$ The FPro S spray gun delivers perfect quality finish for all skill levels
- **2** Patented Vortex delivers perfect atomization with very high transfer efficiency (Vortex uses spinning effect)
- $oldsymbol{3}$ Three different adjustment knobs to achieve the perfect spray pattern for every condition

Productivity

- 4 Perfectly balanced for reduced Carpal Tunnel injuries
- **5** The FPro S is an extension of the arm and user-friendly spray gun designed for all painters
- **6** Reduced trigger pull for fatigue-free painting
- **6** Suction booster valve provides enhanced suction power
- 7 Ergonomic handle ideal for operators with small hands

Sustainability

- **8** FPro S has an elegant design and is made of high quality anodized, machined metal. It is the ultimate spray gun solution for your application needs
- **8** Reduced number of components for quick and simple maintenance
- **9** Reusable aluminum cup with a simplified clamping system
- **10** 3M adaptor available for painters who prefer to use 3M disposable cups for small quantities
- 11 Lightweight spray gun available with an ultra-flexible air hose for effortless use and ergonomic handling



Bond | Protect | Beautify www.sames.com