

## Equipment

Designation	Pressure	Tip type	Tip size	Fitting	Trigger	Part number
SFLOW UNIV 275 2F W/O TIP GUARD W/O SF	275 bar (4020 psi)	-	-	M1/2" JIC	2 fingers	135741201
SFLOW UNIV 275 4F W/O TIP GUARD W/O SF	275 bar (4020 psi)	-	-	M1/2" JIC	4 fingers	135741401
SFLOW UNIV 275 2F FLAT TIP GUARD W/O TIP 1/2 JIC	275 bar (4020 psi)	Flat	-	M1/2" JIC	2 fingers	135741200
SFLOW UNIV7/8 470B 4F FLAT GUARD W/O TIP SF 1/4NPSM	470 bar (6800 psi)	Flat	-	Swivel M1/4 NPSM	4 fingers	135746440
SFLOW UNIV 275 2F REV TIP GUARD 12-13 (515) TIP SF 1/2 JIC	275 bar (4020 psi)	Reversible	12-13 (515)	Swivel M1/2" JIC	2 fingers	135741225
SFLOW UNIV 275 4F REV TIP GUARD 14-13 (517) TIP SF 1/2JIC	275 bar (4020 psi)	Reversible	14-13 (517)	Swivel M1/2" JIC	4 fingers	135741427
SFLOW UNIV7/8 470B 4F REV TIP 18-13 (519) TIP SF 1/2 JIC	470 bar (6800 psi)	Reversible	18-13 (519)	Swivel M1/2" JIC	4 fingers	135746429
SFLOW UNIV7/8 470B 4F REV TIP 18-13 (519) TIP SF 1/4NPSM	470 bar (6800 psi)	Reversible	18-13 (519)	Swivel M1/4 NPSM	4 fingers	135746449

## Accessories

Designation	Part number
AIRLESS FLAT TIP CALIBER XXXX	00000XXXX
AIRLESS SKILL TIP CALIBER XXXX	00030XXXX
TIPTOP AIRLESS REVERSIBLE TIP CALIBER XXXX	00040XXXX
SWIVEL FITTING NG22 500BAR MF1/2" JIC	129732425
SWIVEL FITTING NG22 500B F1/2" JIC M1/4NPS	129732435
PACK OF 4 GUN FILTERS INOX RED 200 MESH / 75µ	129740081
PACK OF 4 GUN FILTERS INOX BLUE 150 MESH / 100µ	129740082
PACK OF 4 GUN FILTERS INOX YELLOW 100 MESH / 150µ	129740083
PACK OF 4 GUN FILTERS INOX WHITE 50 MESH / 300µ	129740084
PACK OF 4 GUN FILTERS PA RED 200 MESH / 75µ	129740181
PACK OF 4 GUN FILTERS PA BLUE 150 MESH / 100µ	129740182
PACK OF 4 GUN FILTERS PA YELLOW 100 MESH / 150µ	129740183
PACK OF 4 GUN FILTERS PA WHITE 50 MESH / 300µ	129740184
TIP NUT M7/8" WITH plastic HANDGUARD FOR TIP TOP REVERSIBLE TIP	132740210
TIP NUT M7/8" WITH metallic HANDGUARD For Skill® or flat tips	132746100

## Kits

Designation	Version	Suction rod	Pump filter	Hose length	Whip end	Gun	Gun filter	Tip guard	Tip	Part number
W/M KIT AIRLESS 30C25 MBA SUC+FILT+SFLOW7/8-275 2F SKILL0913	Wall mounted	25 mm (1")	X	7.5m (25 ft)	1.6m (5ft)	Sflow® 275 7/8 (2F)	♦	Flat	Skill® 09-13	151265016
MOB KIT AIRLESS 30C25 MBA SUC+SFLOW7/8-275 2F TIPTOP1213	Trolley	25 mm (1")	-	7.5m (25 ft)	1.6m (5ft)	Sflow® 275 7/8 (2F)	♦	Reversible	Tip Top 12-13	151265017
MOB KIT AIRLESS 35C50 MBA SUC+FILT+SFLOW7/8-275 2F TIPTOP1213	Trolley	25 mm (1")	X	7.5m (25 ft)	1.6m (5ft)	Sflow® 275 7/8 (2F)	♦	Reversible	Tip Top 12-13	151265018
MOB KIT AIRLESS 40C100 MBA SUC+FILT+SFLOW7/8-275 4F TIPTOP1413	Trolley	25 mm (1")	X	7.5m (25 ft)	1.6m (5ft)	Sflow® 275 7/8 (4F)	♦	Reversible	Tip Top 14-13	151265019

## Spare Parts

Designation	Part number
2 finger trigger	129740006
4 finger trigger	129740007
Maintenance set for SFlow® 275 (needle and spring)	129740901
Maintenance set for SFlow® 470 (needle and spring)	129740902



13 chemin de Malacher - CS 70086  
38243 Meylan Cedex - FRANCE  
Phone: +33 (0)4 76 41 60 60 - Fax: +33 (0)4 76 41 60 90  
www.sames.com

SAMES reserves the right to modify its equipment or specifications without further notice. Document, products and pictures shown are not contractual. Address is a registered trademark. FR: n° 1 222 301 - 200305 - 573.724.002 (NA LTH 999-400-327)

## SFlow® Universal 7/8"

Manual Airless Paint Sprayer

Airless / Manual Guns



NO NEED TO BE ROUGH TO BE STRONG

- High transfer efficiency of 81%
- Good atomization quality
- 7/8" Universal front thread tip guard

## Markets



AGRICULTURAL



CONSTRUCTION



INDUSTRIAL



TRANSPORTATION

BOND • PROTECT • BEAUTIFY



# SFlow® Universal 7/8"

Manual Airless Paint Sprayer

The Sflow® 7/8" Universal Airless paint sprayer provides all the benefits of the Sflow® 275 and 470 bar (4000 & 6820 psi). It is fully compatible with every tip guard on the market with a Universal front thread. The ergonomic design offers flexibility in extreme conditions and is ideal for handling high solid content paints and high rich zinc primers.

The SFlow® Universal Airless manual paint sprayers deliver real material savings for industrial applications with a transfer efficiency of 81%. Its reliable and solid construction combined with a comfortable grip and fatigue-free trigger makes finishing so easy even under the toughest conditions. SFlow® Airless manual spray gun optimizes efficiency and delivers great comfort to the finisher. A large choice of tips are available for every application need: Flat, Reversible TipTop or Skill® (double insert).



## Technical data table

Designation	Value	Unit: metric (US)
Maximum Fluid Pressure	275 (4000) - 470 (6820)	bar (psi)
Transfer Efficiency	81	%
Maximum Fluid Temperature	60 (140)	°C (°F)
Fluid Inlet	M 1/2 JIC / M 1/4 NPSM	
Smooth Swivel	M 1/2 JIC / M 1/4 NPSM	
Trigger Lock Safety	♦	
Polished Forged Aluminum Body	♦	
Recommended Material Viscosity Range	20s à 25000 cps	s CA4
Sound Level	88.6	dbA
Stainless Steel, Aluminium and Rulon Wetted Parts	♦	
Carbide Seat	♦	
Fluid Swivel Fitting (available upon version)	♦	
Weight	597 (21)	g (oz)



## Technologies




Chevron Sealing



Reversible Tip



Airless spray technology



Skill Tip



## Description

### Performance

- 1 Reliable & repeatable spraying quality: high-end tungsten carbide tip tested
- 3 Embedded patented dedicated tool for quick filter changes
- 8 Large choice of flat, Skill® or reversible tips to meet your requirements
- ♦ Enhanced security: Trigger lock, tip lock, and hand safety protection

### Productivity

- 2 Fatigue-free, (2) or (4) finger trigger to fit every painters' needs
- 4 Ergonomic design with comfortable grip to prevent any RSI.
- 5 Built-in hook allows you to keep the gun near the work station
- 6 Swivel fitting for better maneuverability
- 7 Universal 7/8" thread tip guard for easy tip orientation and positioning

### Sustainability

- 3 Large filtration hand filter area: available in PA or stainless steel to prevent any tip plugging
- 3 Material flow from inside to outside of the filter for easier maintenance.
- ♦ Patented trigger guard: acts as a wrench, a filter extractor and helps to remove trigger

