

**Material Safety Data Sheet**

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

HI SOL 10

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: HI SOL 10

General or Generic ID: AROMATIC HYDROCARBON

FAMIS, Inc.
5689 NW 35th Ct.
Miami, FL 33142

Regulatory Information Number
Telephone
Emergency telephone number

305-638-8810
305-638-8810
1-800-CHEMTREC
(1-800-243-6873)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
AROMATIC PETROLEUM DISTILLATES	64742-95-6	98.0-100.0
1,2,4-TRIMETHYLBENZENE	95-63-6	36.0- 36.0
1,3,5-TRIMETHYLBENZENE	108-67-8	7.0- 11.0
DIETHYLBENZENE	25340-17-4	1.0- 5.0
XYLENE	1330-20-7	1.5- 1.5
ISOPROPYLBENZENE	98-82-8	1.5- 1.5

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Additional symptoms of eye exposure may include: blurred vision.

Skin

Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and



Material Safety Data Sheet

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

cracking of skin, burns and other skin damage. Additional symptoms of skin contact may include: skin blistering, Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: redness of the face and neck, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, temporary changes in behavior, effects on memory, muscle weakness, mild, temporary changes in the liver, respiratory depression (slowing of the breathing rate), shortness of breath, loss of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), respiratory failure, coma.

Target Organ Effects

This material (or a component) has been shown to lower activity of certain immune system cells in experimental animals. The significance of this effect with respect to human health is uncertain. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: blood abnormalities, liver abnormalities, cataracts, kidney damage, effects on hearing, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: liver abnormalities.

Developmental Information

This material (or a component) may be harmful to the human fetus based on positive test results with laboratory animals. Cumene (isopropylbenzene) did not cause harm to the unborn pup in

Material Safety Data Sheet

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

laboratory animal studies, even at levels which were harmful to the pregnant animal.

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion.

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems)

**Material Safety Data Sheet**

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions), liver, kidney, blood-forming system, immune system, auditory system, eye, Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

5. FIRE FIGHTING MEASURES

Flash Point

100.0 - 110.0 F (37.7 - 43.3 C) TCC

Explosive Limit

(for product) Lower 1.0 Upper 7.0 %

Autoignition Temperature

910.0 F (487.7 C)

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Extinguishing Media

regular foam (such as AFFF), carbon dioxide, dry chemical.

Fire Fighting Instructions

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

NFPA Rating

Health - 1, Flammability - 2, Reactivity - 0

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent, or other absorbent material and transfer to hood.

Material Safety Data Sheet

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

7. HANDLING AND STORAGE**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Storage

Store in a cool, dry, ventilated area. Do not store near extreme heat, open flame, or sources of ignition. Store out of direct sunlight.



Material Safety Data Sheet

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

AROMATIC PETROLEUM DISTILLATES (64742-95-6)
No exposure limits established

1,2,4-TRIMETHYLBENZENE (95-63-6)
ACGIH TLV 25.000 ppm - TWA

1,3,5-TRIMETHYLBENZENE (108-67-8)
ACGIH TLV 25.000 ppm - TWA

DIETHYLBENZENE (25340-17-4)
No exposure limits established

XYLENE (1330-20-7)
OSHA PEL 100.000 ppm - TWA
OSHA VPEL 100.000 ppm - TWA
OSHA VPEL 150.000 ppm - STEL
ACGIH TLV 100.000 ppm - TWA
ACGIH TLV 150.000 ppm - STEL
OTHER LIMIT 46.000 ppm - TWA

**Material Safety Data Sheet**

Revision Date: 11/30/2005

Print Date: 3/2/2023

MSDS Number: SOL10

SOL10 HI-SOL 10

ISOPROPYLBENZENE (98-82-8)
OSHA PEL 50.000 ppm - TWA (Skin)
OSHA VPEL 50.000 ppm - TWA (Skin)
ACGIH TLV 50.000 ppm - TWA (Skin)

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for product) 308.0 - 335.0 F (153.3 - 168.3 C) @ 760 mmHg

Vapor Pressure

(for product) 2.100 mmHg @ 68.00 F

Specific Vapor Density

4.500 @ AIR=1

Specific Gravity

.855 - .889 @ 68.00 F

Liquid Density

7.260 lbs/gal @ 68.00 F

.872 kg/l @ 20.00 C

Percent Volatiles

100.0 %

Volatile Organic Compounds (VOC)

100.000 %

876.000 g/l

7.300 lbs/gal

Evaporation Rate

25.00 (ETHER)

Appearance

CLEAR, COLORLESS

State

LIQUID

Physical Form

HOMOGENEOUS SOLUTION

Color

CLEAR, SAYBOLT COLOR 21 MIN

Odor

AROMATIC, STRONG



Material Safety Data Sheet

Revision Date: 11/30/2005

Print Date: 3/2/2023

MSDS Number: SOL10

SOL10 HI-SOL 10

pH

No data

Freezing Point

-63.4 F (-53.0 C)

Molecular Weight

121.0

Solubility in Water

NEGLIGIBLE

Heat Value

18818.000 BTU

Bulk Density

.980 lbs/ft³

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

Incompatibility

Avoid contact with: nitric acid, strong oxidizing agents, sulfuric acid.

11. TOXICOLOGICAL INFORMATION

No data

12. ECOLOGICAL INFORMATION

No data



Material Safety Data Sheet

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC&S Environmental Services Group at 800-531-7106 800-531-7106 .

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:
NON-REGULATED BY D.O.T.

Container/Mode:
55 GAL DRUM/TRUCK PACKAGE

NOS Component:
AROMATIC PETROLEUM DISTILLATES

RQ (Reportable Quantity) - 49 CFR 172.101

Product Quantity (lbs) Component

Product Quantity (lbs)	Component
6667	XYLENES (O-, M-, P- ISOMERS)

Other Transportation Information

The Transport Information may vary with the container and mode of shipment.

15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status
TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4(a)

Component	RQ (lbs)
XYLENES (O-, M-, P- ISOMERS)	100
CUMENE	5000

SARA 302 Components - 40 CFR 355 Appendix A



Material Safety Data Sheet

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive() Sudden Release of Pressure()

SARA 313 Components - 40 CFR 372.65

Section 313 Component(s)	CAS Number	%
1,2,4-TRIMETHYLBENZENE	95-63-6	42.00
XYLENE (MIXED ISOMERS)	1330-20-7	2.10
CUMENE	98-82-8	2.00

OSHA Process Safety Management 29 CFR 1910

None listed

EPA Accidental Release Prevention 40 CFR 68

None listed

International Regulations

Inventory Status

AICS (AUSTRALIA) The intentional ingredients of this product are listed.

DSL (CANADA) The intentional ingredients of this product are listed.

ECL (SOUTH KOREA) The intentional ingredients of this product are listed.

EINECS (EUROPE) The intentional ingredients of this product are listed.

IECSC (CHINA) The intentional ingredients of this product are listed.

PICCS (PHILIPPINES) The intentional ingredients of this product are listed.

State and Local Regulations

California Proposition 65

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer.

ETHYL BENZENE
BENZENE

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause reproductive harm.

TOLUENE
BENZENE

**Material Safety Data Sheet**

Revision Date: 11/30/2005

Print Date: 3/2/2023

SOL10 HI-SOL 10

MSDS Number: SOL10

New Jersey RTK Label Information

PSEUDOCUMENE	95-63-6
1,3,5-TRIMETHYLBENZENE	108-67-8
DIETHYLBENZENE	25340-17-4
XYLENES	1330-20-7
CUMENE	98-82-8

Pennsylvania RTK Label Information

PSEUDOCUMENE	95-63-6
BENZENE, DIMETHYL-	1330-20-7
BENZENE, (1-METHYLETHYL)-	98-82-8

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

Last page