

Equipment

| Designation | Drum size | Elevator height (mm) | Agitator rod length (mm) | Paddle diameter (mm) | cover diameter (mm) | Part number |
|--------------|-------------------|----------------------|--------------------------|----------------------|---------------------|-------------|
| COVER | 20-40 L / 5-11 GI | | | | 400 | 154261600 |
| 40L AGITATOR | 20-40 L / 5-11 GI | | 400 | 134 | | 154261700 |
| SUCTION | 20-40 L / 5-11 GI | | | | | 154261800 |
| 40l ram | | | | | | 151081000 |

Accessories

| Designation | Part number |
|--|-------------|
| 2 L.DRUM - OIL HP 150 FOR DIAPHRAGM PUMP & OILER | 149990017 |
| DRUM ROLLER PLATE 200 L ONLY | 151098100 |
| ARI SUPPLY ASSEMBLY | 154261930 |
| SLOTTED PADDLE | 154261952 |
| AIR FILTER 1/4 | 154261996 |
| AIR LUBRICATOR 1/4 + SUPPORT | 154261997 |

CYCLIX 20-40

Drum Cover Agitators



Airspray / Accessories

AGITATION FOR BEST RESULTS

- Constant quality of mixed materials
- Stainless steel wetted parts
- High ROI - no product lost

Markets



BOND • PROTECT • BEAUTIFY



CYCLIX 20-40

Drum Cover Agitators

Cyclix gear drive agitators for open top 20-40 liter drum feature a stainless steel cover mounted on a single post elevator for quick material changes.

This elevator-agitator for 20-40 to 200 Liter drums features a double-effect jack for a fast lift of a stainless steel cover fitted for a quick material drum change. The cover is equipped with a motorized agitator fitted with blades for low viscosity materials and a full stainless steel rod. The elevator is coming on a large fixing plate which makes it very stable and easy to install in paint kitchens, existing installations or an essential component of new installations



Technical data table


| Designation | Value | Unit: metric (US) |
|----------------------------|-------------------|-------------------|
| Length | 696 (27) | mm (in) |
| Height | 1024-1500 (40-59) | mm (in) |
| Width | 400 (15.7) | mm (in) |
| Recommended Fluid Pressure | 60 (1.40) | bar (psi) |
| Rotation Speed | 150 | l/min (rpm) |
| Torque at 100 rpm | 2.2 | Nm |
| Maximum Air Consumption | 43.2 | m3/h (cfm) |
| Maximum Pressure | 6.9 (100) | bar (psi) |
| Max power | 0.75 | kW |
| Stopping torque | 2.1 | Nm |



Technologies



Airmix® spray technology



Electrostatic



Airless® spray technology



Airspray Conventional



Description

Performance

- ◆ Bi-directional jack for fast lift of stainless steel agitator cover (3 positions available)
- ◆ Quick material change
- ◆ Lubricated air motor - compact with adjustable speed and safe operation

Productivity

- ◆ User-friendly
- ◆ Agitator disengaged during elevator movement

Sustainability

- ◆ Stainless steel cover is compatible with all materials
- ◆ Suction and return tubes benefits suitable for re-circulating

